




ABOVEGROUND/UNDERGROUND PROPANE STORAGE TANKS 120 - 1000 Gallons



PRESSURE VESSEL CODES & REGISTRATION

- Designed and constructed in accordance with the ASME Section VIII Division I Code
- Registered with the National Board of Boiler & Pressure Vessels Inspectors
- Complies with NFPA 58
- Conforms to specifications set forth by the Railroad Commission of Texas

PAINT SPECIFICATIONS

- Super durable TGIC polyester powder paint for maximum rust protection
- Standard tanks painted Sky White, custom colors available upon request
- Product used underground will need to be field painted accordingly for such an application
- Ready to bury durable epoxy powder coating*



MADE IN THE U.S.A.

VESSEL FEATURES

- Tanks fully fitted with RegO valves and Rochester liquid level gauges
- Dual service options for aboveground or underground applications
- Product supplied with steel dome (custom colors available upon request) or plastic AG/UG shroud, specify at time of order
- Container pressure rated at 250 PSI @ 400°F
- Vacuum pre-purged
- Stainless steel data plate
- Anode bolt connection located under the dome
- #54 liquid level outage valve orifice
- Made in the U.S.A

PROCESS CONTROL

All welded products are x-rayed and pressure tested @ 325 PSI per ASME Sec VII, Div I requirements, followed by rigorous leak test inspections, both pre and post valving

GENERAL MAINTENANCE REQUIREMENTS

Contact Propane Education & Research Council for additional resources and information at usepropane.com




ABOVEGROUND/UNDERGROUND PROPANE STORAGE TANKS 120 - 1000 Gallons

ABOVEGROUND/UNDERGROUND VESSEL DIMENSIONS & SPECIFICATIONS



(All Vessel Dimensions are Approximate)

Part Number	Description	Water Capacity Gal/l	Outside Diameter In/mm	Head Type	Overall Length In/mm	Overall Height In/mm	Leg Width In/mm	Leg Spacing In/mm	Weight Lbs/kg	Quantity	
										Full Load	Per Stack
68280	120 Gallon AG/UG Storage Tank, White	120 454.2	24" 609.6	Ellip	5' 8" 1727.2	2' 11 7/8" 911.2	10 1/8" 257.3	3' 0" 914.4	312 141.5	96	12
68280.6	120 Gallon AG/UG Storage Tank, Gray	120 454.2	24" 609.6	Ellip	5' 8" 1727.2	2' 11 7/8" 911.2	10 1/8" 257.3	3' 0" 914.4	312 141.5	96	12
68281	250 Gallon AG/UG Storage Tank, White	250 946.3	30" 762	Hemi	7' 10" 2387.6	3' 5 7/8" 1063.6	12 3/4" 323.9	3' 6" 1066.8	473 214.5	54	9
68281.6	250 Gallon AG/UG Storage Tank, Gray	250 946.3	30" 762	Hemi	7' 10" 2387.6	3' 5 7/8" 1063.6	12 3/4" 323.9	3' 6" 1066.8	473 214.5	54	9
68282	320 Gallon AG/UG Storage Tank, White	320 1211.3	30" 762	Hemi	9' 7" 2921	3' 6 9/16" 1081.1	12 3/4" 323.9	4' 0 1/4" 1225.6	567 257.2	45	9
68282.6	320 Gallon AG/UG Storage Tank, Gray	320 1211.3	30" 762	Hemi	9' 7" 2921	3' 6 9/16" 1081.1	12 3/4" 323.9	4' 0 1/4" 1225.6	567 257.2	45	9
68283	500 Gallon AG/UG Storage Tank, White	500 1892.7	37.5" 952.5	Hemi	9' 10" 2997.2	4' 2 7/16" 1281.1	15" 381	5' 0" 1524	921 417.8	30	6
68283.6	500 Gallon AG/UG Storage Tank, Gray	500 1892.7	37.5" 952.5	Hemi	9' 10" 2997.2	4' 2 7/16" 1281.1	15" 381	5' 0" 1524	921 417.8	30	6
68284	1000 Gallon AG/UG Storage Tank, White	1000 3785.4	41" 1041.4	Hemi	15' 11" 4851.4	4' 5 3/8" 1355.7	16 1/4" 412.8	9' 0" 2743.2	1812 821.9	15	5
68284.6	1000 Gallon AG/UG Storage Tank, Gray	1000 3785.4	41" 1041.4	Hemi	15' 11" 4851.4	4' 5 3/8" 1355.7	16 1/4" 412.8	9' 0" 2743.2	1812 821.9	15	5

* Federal, state or local regulations may contain specific applicable requirements for protective coatings and cathodic protection. The purchaser and installer are responsible for compliance with such federal, state, local and NFPA industry regulations, including, but not limited to, proper purging prior to putting into service. Cathodic protection is required. Coating (s) must be continuous, uninterrupted and must comply with local, state or national codes or regulations.



FITTING LAYOUT



MADE IN THE U.S.A.