

ø9/16 HOLES ON A
8.1/2 BOLT CIRCLE
TYP. 4 PLCS.

- NOTES:
- FOR NON-CORROSIVE SERVICE.
 - INTERIOR OF VESSEL TO BE CLEAN, DRY, & FREE OF MOST RUST, DIRT, OIL, SLAG, & OTHER FOREIGN PARTICULATE MATTER.
 - SEAL WELDED NAMEPLATE.

SPECIFICATIONS

O.D.	10	LGTH.	25.1/4	HEAD (H1):	MAT'L.	MAWP	250	PSI @	120°F
WT.	34	LBS.		HEAD (H2):	MAT'L.	TEST	PSI		
S.A.	5.8	SQ.FT.		SHELL:		RT-	MDMT: -20°F @	250	PSI
GAL.	7.7	CU.FT.	1.02	CRN:	N9270.2513	X-RAY:	W		
CODE:	ASME SEC. VIII DIV. I, LATEST EDITION				CORR	ALW	SH	HD	
STD. TOLERANCES:	M-2461 (UNLESS OTHERWISE NOTED)				WELD DETAILS:	M-1932			




VERTICAL GAS SCRUBBER

FILE LOCATION: MTEFRAT.APPS\$\DWG\301

RELEASED FOR PRODUCTION

Q.C. _____ DATE _____

UNLESS OTHERWISE SPECIFIED ALL DIMENSIONS ARE IN: **INCHES**



SYM	DATE	BY	REVISION	APP	REV
E		DS		DS	
F		BC		BC	
A		EGB		EGB	
B		JPR		JR	
C		TA		MR	
D		CM		DW	

DRAWN BY:	DATE:
LB	
APPR. BY:	DATE:
AS	
SCALE:	DRWG NO.
NONE	301301